

I&M SERIES ORDER DATA

SERIES

I SINGLE ROD END, 1.25 THRU 5.00 IN. BORE
 DI DOUBLE ROD END, 1.25 THRU 5.00 IN. BORE
 M SINGLE ROD END, 6.00 AND 8.00 IN. BORE
 DM DOUBLE ROD END, 6.00 AND 8.00 IN. BORE
 A AIR OIL TANK 1.75 THRU 8.00 IN. BORE

MOUNTS
 EYE MOUNT
 CLEVIS MOUNT AND PIN
 ROD CLEVIS AND PIN
 END LUG MOUNTS
 FRONT FLANGE MOUNT
 REAR FLANGE
 FRONT TRUNION MOUNT
 REAR TRUNION MOUNT

EM
 CM&P
 RC&P
 EL
 FF
 RF
 FTM
 RTM

STROKE

INCH OF STROKE AND OR FRACTION

I

125

X

4

CR

CM&P

ROD EXT. 1.00

BORE CODE	BORE SIZE		AREA	RETRACT
	BORE INCHES	EXTEND		
125	1.25	1.23	1.12	
175	1.75	2.40	1.96	
200	2.00	3.14	2.70	
250	2.50	4.91	4.47	
300	3.00	7.07	6.62	
350	3.50	9.62	8.84	
450	4.50	15.90	15.12	
500	5.00	19.63	18.85	
600	6.00	28.27	26.50	
800	8.00	50.26	48.50	

OPTIONS

BUMPER ROD END
 BUMPER BLIND END
 BUMPER ROD AND BLIND
 1 IN CUSHION ROD END
 1 IN CUSHION BLIND END
 1 IN CUSHION BOTH ENDS
 2 IN CUSHION ROD END
 2 IN CUSHION BLIND END
 2 IN CUSHION BOTH ENDS
 1 TO 3 IN. SPRING RETURN
 STANDARD STYLE TWO ROD END
 STANDARD STYLE THREE ROD END
 MAGNETIC PISTON
 METALLIC ROD SCRAPER
 POLYPAK ROD SEAL
 VITON SEALS

OPTIONS TO BE SPELLED OUT

ROD EXTENSION
 SPECIAL NUMBER 1 ROD END, FULL MALE
 SPECIAL NUMBER 2 ROD END, MALE TURN DOWN
 SPECIAL NUMBER 3 ROD END, FEMALE
 PORT LOCATION, 1,2,3,4
 ADJUSTABLE EXTEND STROKE
 EXTENDED TIE RODS ROD END
 EXTENDED TIE RODS BLIND END
 303 STAINLESS CHROME ROD
 STAINLESS TIE RODS, LOCK WASHER, NUTS
 STOP TUBE (1 INCH STANDARD)

BR
 BB
 BR&BB
 CR
 CB
 C
 CR2
 CB2
 C2
 SR
 S2
 S3
 M
 MRW
 PP
 V