

C SERIES ORDER DATA

SERIES

C	SINGLE ROD END
DC	DOUBLE ROD END
CSR	SINGLE ROD END SPRING RETURN
CSE	SINGLE ROD END SPRING EXTEND
DCSR	DOUBLE ROD END SPRING RETURN

STANDARD STROKES

BORE	BORE	BORE	BORE	BORE	BORE	BORE
1/2	3/4	1 1/8	1 5/8	2.00	2 1/2	3.00
.062	.125	.125	.125	.125	.125	.125
.125	.187	.250	.250	.250	.250	.250
.250	.250	.500	.500	.375	.500	.500
.375	.375	.500	.750	.500	.750	.750
.500	.500	.750	1.00	.750	1.00	1.00
.625	.625	1.00	1.50	1.00	1.50	1.50
.750	.750	1.25	2.00	1.50	2.00	2.00
1.00	1.00	1.50	3.00	2.00	3.00	3.00
1.25	1.25	1.75	4.00	3.00	4.00	4.00
1.50	1.50	2.00		4.00		
2.00	2.00	3.00				
3.00	3.00	4.00				
4.00	4.00					

MOUNTS
 CLEVIS MOUNT AND PIN CM&P
 ROD CLEVIS AND PIN RC&P

C 1 1/8 X 4.00

BORE SIZE

BORE CODE	BORE INCHES	AREA EXTEND	AREA RETRACT
1/2	.500	.19	.14
3/4	.750	.44	.37
1 1/8	1.125	.99	.80
1 5/8	1.625	2.0	1.76
2.00	2.000	3.14	2.70
2 1/2	2.500	4.91	4.47
3.00	3.000	7.07	6.62
4.00	4.000	12.57	11.97

V

OPTIONS
 VITON SEALS V
 MALE ROD END MR
 NON-ROTATING NR
 CHROME ROD CR
 BUMPER ROD END BR
 BUMPER BLIND END BB
 BUMPER ROD AND BLIND BR&BB

CM&P

ROD EXT 1.00

OPTIONS TO BE SPELLED OUT
 ROD EXTENSION
 SPECIAL ROD THREAD